

IR Vari-focus Dome Network Camera

Product Type

IR Vari-focus Dome Network Camera

Product Model

BSR-IPA410-Z



Key Features

- ✧ 1.3MP (1280×960) high resolution
- ✧ Smart video detection
- ✧ 2.8-12mm vari-focus lens
- ✧ Up to 30m IR visibility
- ✧ True day/night
- ✧ 3D DNR & DWDR & BLC
- ✧ IP66 rating
- ✧ Vandal-proof housing
- ✧ External PoE

Specifications

| Parameters/Model | | BSR-IPA410-Z |
|------------------|-------------------------|--------------------------------------|
| Camera | Image Sensor | 1/3" Progressive Scan CMOS |
| | Min. Illumination | 0.1Lux@(F1.2), AGC ON, 0 Lux with IR |
| | Shutter Time | 1/25s--1/10,000s |
| | Lens | 2.8-12mm@F1.4(6-22mm optional) |
| | Lens Mount | φ14 |
| | Digital Noise Reduction | 3D DNR |
| | Wide Dynamic Range | Digital WDR |
| | Day & Night | IR cut filter with auto switch |
| Compression | Video Compression | H.264/MJPEG |

| Parameters/Model | | BSR-IPA410-Z |
|------------------|--------------------------|---|
| Standard | H.264 Codec Profile | Main Profile |
| | Bit Rate | 64Kbps—8Mbps |
| | Dual Stream | Yes |
| Image | Max. Image Resolution | 1280×960 |
| | Frame Rate | 30fps(1280×960) 25fps(1280×720) |
| | Image Settings | Saturation, brightness, contrast, sharpness adjustable through client software or browser |
| | BLC | Yes, zone configurable |
| | Video Active Enhancement | Yes |
| Network | Alarm Trigger | Motion detection, abnormality alarm, video block alarm |
| | Protocols | TCP/IP , RTP , UDP , HTTP , DHCP , DDNS , PPPoE , NTP |
| | System Compatibility | ONVIF |
| Interface | Communication Interface | 1 RJ45 10M/100M Ethernet Interface |
| General | Operation Conditions | -10°--55°(); humidity 95% or less |
| | Power Supply | 12VDC ±10% ; PoE(802.3af) |
| | Power Consumption | Max.5W |
| | Ingress Protection | IP66 |
| | IR Range | 30m |
| | Dimensions | 150(L)*105(H)mm |
| | Weight | 650g |

Typical Applications

Suitable for financial, military, prisons, airports, factories, government, hotels, such as IP monitoring, especially suitable for the night, such as outdoor, warehouses and other locale with auxiliary infrared light source.

Picture



Dimensions

